



## Low Dropout Linear Voltage Regulator

### ● Features

- Low Power Consumption 65 $\mu$ A
- Dropout Voltage: 150mV @ 100mA
- Output Current: more than 200mA
- Thermal Shutdown Protection
- Highly Accurate:  $\pm 2\%$
- Typical 300mA Current Limit

### ● Applications


- Battery powered equipment
- Reference voltage sources
- Cameras, Video cameras
- Portable AV systems
- Mobile phones
- Communication tools

### ● General Description


The FS3302B series are CMOS precise, low power consumption, high voltage; positive voltage regulators designed for portable applications with low quiescent current ( 65 $\mu$ A ) and dropout voltage ( 150mV at 100mA ).

The FS3302B have typical current limit of 300mA and are available in high accuracy ( 2% ), The output voltages are 1.2V、1.5V、1.8V、2.0V、2.5V、3.0V、3.3V 、5.0V and adjust. These products feature thermal shutdown protection and current limit with fold-back in short circuit. SOT23 packages are available.

### ● Pin Configurations (SOT23-3L)



### ● Typical Application Circuit



### ● Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
IN Supply Voltage	V <sub>IN</sub>	-0.3 TO 8	V
OUT Voltage	V <sub>OUT</sub>	-0.3V to V <sub>IN</sub> +0.3	V
Continuous OUT Current	I <sub>MAX</sub>	Internally limited	A
Power Dissipation ( T <sub>AMB</sub> = 25°C )	P <sub>D</sub>	150	mW
Operating Temperature	T <sub>OPR</sub>	-25 to +85	°C
Storage Temperature Range	T <sub>STG</sub>	-40 to +125	°C



● **Ordering Information**

FS3302B-①②③④


DESIGNATOR	SYMBOL	DESCRIPTION
①②	Output Detection Voltage	...12=1.2V 15=1.5V, 18=1.8V, 28=2.8V, 30=3.0V, 33=3.3V
③④	Package Type:	SI: SOT23-3L

● **Electrical Characteristics**

$V_{IN} = V_{OUT} + 1V$ ,  $C_{IN} = C_{OUT} = 1\mu F$ ,  $T_J = 25^\circ C$  unless otherwise specified

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Operating Voltage	$V_{IN}$		2.5		5.5	V
Output Voltage Accuracy	$\Delta V_{OUT}$		-2	0	2	%
Line Regulation		$V_{IN} = V_{OUT} + 1V$ to 8V		6		mV
Load Regulation		$I_{OUT} = 1mA$ to 100 mA		20		mV
Power Supply Rejection Ratio	PSRR	$V_{IN} = V_{OUT} + 1V_{P-PAC}$ , $F = 1 KHz$ , $I_{OUT} = 40mA$ $C_{OUT} = 1\mu F$		60		dB
Supply Current	$I_Q$			65	90	$\mu A$
Dropout Voltage	$V_{DROP}$	$I_{OUT} = 100mA$		140	170	mV
Current Limit	$I_{LIM}$			300		mA
Current Limit Short Circuit	$I_{LIMSC}$			80		mA
Output Noise	$e_n$	$C_{OUT} = 1\mu F$ , $I_{OUT} = 40mA$ , $F = 300Hz$ to 50KHz		50		$\mu V_{RMS}$

● **Typical Block Diagram**





● Typical Performance Characteristics




Figure 1. Output Voltage vs. Output Current




Figure 2. Output Voltage vs. Input Voltage




Figure 3. Dropout Voltage vs. Output Current




Figure 4. Quiescent Current vs. Input Voltage




Figure 5. CE PIN Current vs. CE PIN Voltage




Figure 6. Power Supply Rejection Ratio



● Typical Performance Characteristics




Figure 7. Quiescent Current vs. Ambient Temperature




Figure 8. Quiescent Current vs. Ambient Temperature




Figure 9. CE Pin Current vs. Ambient Temperature





Figure 10. Output Voltage vs. Ambient Temperature



● Package Information

SOT-23 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP.		0.037 TYP.	
e1	1.800	2.000	0.071	0.079
L	0.550 REF.		0.022 REF.	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°